



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-50GHz
 VSWR: DC-50GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1.
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHING.

LTR	DESCRIPTION	DATE	APPR.

2.4mm Connector

DWG NO. D371S12F06

OUTLINE DRAWING

SIZE: A4_h SCALE: 1 REV: V2.0 SHEET 1/1