



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-65GHz
 VSWR: DC-65GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT: mm

DRAWN: Xin Gong
 CHECKED: Min Hai Zhang
 APPR: Gang Cao

DWG NO.

D380S09F04

1.85mm Connector

LTR	DESCRIPTION	DATE	APPR.

1. CHECK ALL DIMENSIONS, ALL CORNERS, SHARP EDGES, 0.40 R MAX UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS NOTED.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER FINISHING. SURFACE FINISHED.
 DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V2.0 SHEET 1/1

OUTLINE DRAWING

1 2

5 6