



**Performance Features:**

Nominal Impedance: 50 $\Omega$   
 Frequency Range: DC-65GHz  
 VSWR: DC-65GHz.... 1.25:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganabahu Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALIWINTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.

**DIRECTION OF VIEW**

Top View:

Front View:

**UNIT**  
mm

**TITLE**  
1.85mm Connector

**DWG NO.**  
D380S12F05

**OUTLINE DRAWING**

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING	SIZE: A4_h	SCALE: 4:1	REV: V2.0	SHEET 1/1
----------------------	------------	------------	-----------	-----------

1 2

5 6