



SOCKET TO ACCEPT $\phi 0.30(.012")$
PIN 2(.079") MAX DEPTH

Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-65GHz
 VSWR: DC-65GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganachua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

UNIT
 mm

TITLE
1.85mm Connector

DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

DWG NO.
D380S12Y02

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE: A4-h SCALE: 4:1 REV: V2.0 SHEET 1/1