



SOCKET TO ACCPET $\phi 0.46(.018)$ PIN
2.5(.098") MAX DEPTH

Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304980
 FAX: 025-84304989
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.



DIRECTION OF VIEW

UNIT
mm

TITLE
N Connector

DWG NO.
D340S18F01

APPR.	Shaoqing Du	DRAWN	Haolin Zhang	CHECKED	GAO Cao
APPR.		APPR.		APPR.	
LTR	DESCRIPTION	DATE	APPR.		

UNLESS OTHERWISE SPECIFIED:
 1. FINISH: ALL DIMENSIONS, SURFACE, UNLESS SPECIFIED, TO BE CONFORMANCE WITHIN G.1
 2. DIMENSIONS ON COMMON CENTERS TO BE CONFORMANCE WITHIN G.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISH

DO NOT SCALE DRAWING

SIZE A4_h SCALE: 1 REV. V2.0 SHEET 1/1