



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PTFE&PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganabua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm
	mm

DRAWN	Xin Gong
CHECKED	Min hai Zhang
APPR.	Gang Cao

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.  
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER PLATING. SOURCE FINISHING.

LTR	DESCRIPTION	DATE	APPR.

TITLE  
**N Connector**

DWG NO.  
**D341S20F10**

**OUTLINE DRAWING**

SIZE	A4_h	SCALE	3:1	REV.	V2.0	SHEET	1/1
------	------	-------	-----	------	------	-------	-----