



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganachua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm
	mm

DRAWN	Xin Gong
CHECKED	Min hai Zhang
APPR.	Gang Cao

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CIRCULAR CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON CORNERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.
 4. ALL DIMENSIONS ARE AFTER FINISHING. SOURCE FINISHING.

DO NOT SCALE DRAWING

TITLE
N Connector

DWG NO.
D341S36F10

OUTLINE DRAWING

SIZE A4_h SCALE REV. V2.0 SHEET 1/1