



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-18GHz

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganabua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

UNIT
 mm

TITLE
 N Connector

DRAWN Shaoqing Du
CHECKED Haimin Zhang
APPR. Gang Cao

DWG NO.
 D341M0306F09

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.

DO NOT SCALE DRAWING

LTR DESCRIPTION DATE APPR.

SIZE A4_h **SCALE:** 1 **REV.** V2.0 **SHEET** 1/1

1 2 3 4 5 6