



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganabua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT
mm

DRAWN: Shaogqing Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

DWG NO.
D540S18F01

TITLE
TNCA Connector

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.

DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V2.0 SHEET 1/1

LTR DESCRIPTION DATE APPR.

1 2

5 6