



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz..... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PTFE&PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganeshua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm

DRAWN	Min Zhou
CHECKED	Shaoping Du
APPR.	Gang Cao

1. UNLESS OTHERWISE SPECIFIED:  
 1. HOLE, ALL DIMENSIONS ARE IN MILLIMETERS, SHOW DECIMALS TO 0.05 MM  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1  
 3. ALL DIMENSIONS ARE AFTER FINISHING, UNLESS OTHERWISE SPECIFIED  
 4. ALL DIMENSIONS ARE AFTER FINISHING, UNLESS OTHERWISE SPECIFIED

DO NOT SCALE DRAWING

TITLE  
**TNCA Connector**

DWG NO.  
**D540S15F09**

**OUTLINE DRAWING**

SIZE: A4\_h SCALE: 1:1 REV: V2.0 SHEET 1/1