



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-40GHz.... 1.20:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganahua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm
	mm

DRAWN	Xin Gong
CHECKED	Haijin Zhang
APPR.	Gang Cao

1. UNLESS OTHERWISE SPECIFIED:
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 3. HATCHES ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER MATING. SURFACE FINISHED

LTR	DESCRIPTION	DATE	APPR.

TITLE
SSMA Connector

DWG NO.
D571S18F02

OUTLINE DRAWING

SIZE	A4_h	SCALE	1:1	REV.	V2.0	SHEET	1/1
------	------	-------	-----	------	------	-------	-----

1 2

5 6