



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-27GHz  
 VSWR: DC-40GHz.... 1.20:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PTFE&PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganachua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW	Shaoping Du	UNIT	mm
CHECKED	Haijin Zhang		
APPR.	Gang Cao		

TITLE	SSMA Connector
DWG NO.	D571S15F07

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING	SIZE: A4_h	SCALE: 4:1	REV. V2.0	SHEET 1/1
----------------------	------------	------------	-----------	-----------

1 2

5 6