



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION ON THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW
 UNIT
 mm

DRAWN Shaoqing Du
CHECKED Haijin Zhang
APPR. Gang Cao

1. EXAMINE ALL DIMENSIONS, ALL CORNERS, SHARP EDGES, 0.40 R MAX
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER MATING. SURFACE FINISHED
DO NOT SCALE DRAWING

TITLE
SSMA Connector

DWG NO.
D570M0616F07C

OUTLINE DRAWING

SIZE A4-h **SCALE**: 4:1 **REV.** V2.0 **SHEET** 1/1